

RSA Via L&G Connector Data Sheet for SLES Linux



Table of Contents

Purpose	3
Supported Software	3
Prerequisites	3
Configuration	4
<i>General</i>	4
<i>Settings</i>	5
<i>Capabilities</i>	5
Command	5
1. Create an account	6
2. Update an account	7
3. Reset account's password	9
4. Add an account to a group	11
5. Remove an account from a group	11
6. Enable an account	13
7. Disable an account	14
8. Create a group	15
9. Delete a group	16

Purpose

This data sheet provides the configuration information required to create a new SLES *Linux* connector.

Supported Software

RSA Via L&G Version 6.8.1, 6.9.1 and above.

Application: SLES *Linux*

Prerequisites

SSH (sshd) server should be running on the host SLES Linux machine.

Note: By default this server is up and running on Linux machine.

Configuration

The Connector creation is made up of three sections:

General – General details about the Connector; viz. the name, type etc.

Settings – The connection settings required to connect the RSA-IMG and the End-point Application in consideration.

Capabilities – These are the list of “verbs” or capabilities that the RSA-IMG Connector supports; for e.g. “Create, Update, Delete, etc.”

General

The following table helps you with the Parameters asked on the “General” screen while creating the Connector.

Field Name	Value
Name	SLES Linux Connector
Description	SLES Linux Connector
Server	AFX Server
Connector Template	<i>Linux</i>
State	Test
Export As Template	N/A

Note: When you are satisfied your connector is configured properly change the state to Active. No automated provisioning will occur while in the Test state. It is recommended that you test all enabled commands using the Test Connector Settings and Test Connector Capabilities prior to changing to the Active state.

Settings

The following table helps you with the Parameters asked on the “Settings” screen while creating the Connector

Field Name	Value
<i>Host</i>	<Hostname or an IP address of the Linux machine>(e.g. m/c name mymachine or localhost or IP like 192.30.30.124)
<i>Port</i>	<SSH Port Number to the Linux machine>(e.g. 22)
<i>Timeout (milliseconds)</i>	<Connection timeout(milliseconds)> (Default 5000)
<i>Login Name</i>	<i>Login name for the Linux machine</i>
<i>Password</i>	<i>Password to login to the Linux machine</i>

Capabilities

The following table(s) helps you with the Parameters asked when enabling the commands (verbs) on the “Capabilities” screen; while creating the Connector.

Following commands are supported by Linux SLES AFX adapter:

Command

- Create an account
- Update an account
- Reset account's password
- Add an account to a group
- Remove an account from a group
- Enable an account
- Disable an account
- Create a group
- Delete a group

Command Input Parameters

1. Create an account

While defining the “Create an Account” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>
Mapping	<i>\${Account.Name}</i>
Description	<i><Name of the account></i>

Field Name	Value
Parameter Name	<i>Password</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	Yes

Display Name	<i>Password</i>
Mapping	<i>\${AccountTemplate.Password}</i>
Description	<i><Password for account to be created></i>

Command Code

Field Name	Value
Shell Command	<code>useradd \${Account} -p `perl -e 'print crypt("\${Password}","salt")" 2>&1</code>

Note : Password containing ` or \$ will work only if \ is appended before it. e.g To use Abc\$%^ as password, add it as Abc\\$%^.

2. Update an account

While defining the “Update an Account” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No

Display Name	<i>Account Name</i>
Mapping	<i>\${Account.Name}</i>
Description	<i><Name of the account></i>

Field Name	Value
Parameter Name	<i>Home</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Home Directory</i>
Mapping	<i>No Mapping</i>
Description	<i><Home directory></i>

Field Name	Value
Parameter Name	<i>Shell</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes

Is the parameter encrypted?	No
Display Name	<i>Login Shell</i>
Mapping	<i>No Mapping</i>
Description	<i><Login Shell></i>

Command Code

Field Name	Value
Shell Command	<code>usermod -d \${Home} -s \${Shell} \${Account} 2>&1</code>

3. Reset account's password

While defining the "Reset an Account's password" verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>

Mapping	<i>\${Account.Name}</i>
Description	<i><Name of the account></i>

Field Name	Value
Parameter Name	<i>Password</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	Yes
Display Name	<i>Password</i>
Mapping	<i>No Mapping</i>
Description	<i><Initial password to reset to></i>

Command Code

Field Name	Value
Shell Command	<i>echo \${Password} passwd \${Account} --stdin 2>&1</i>

4. Add an account to a group

While defining the “Add an Account to group” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>
Mapping	<i>\${Account.Name}</i>
Description	<i><Name of the account></i>

Command Code

Field Name	Value
Shell Command	<i>usermod -A \${Group} \${Account} 2>&1</i>

5. Remove an account from a group

While defining the “Remove an Account from group” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>
Mapping	<i>\${Account.Name}</i>
Description	<i><Name of the account></i>

Field Name	Value
Parameter Name	<i>Group</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Group Name</i>
Mapping	<i>\${Group.Name}</i>

Description	<Name of the group>
-------------	---------------------

Command Code

Field Name	Value
Shell Command	<code>usermod -R \${Group} \${Account} 2>&1</code>

6. Enable an account

While defining the “Enable an Account” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>
Mapping	<code>\${Account.Name}</code>
Description	<Name of the account>

Command Code

Field Name	Value
Shell Command	<code>passwd -u \${Account} 2>&1</code>

7. Disable an account

While defining the “Disable an Account” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Account</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Account Name</i>
Mapping	<code>\${Account.Name}</code>
Description	<i><Name of the account></i>

Command Code

Field Name	Value
Shell Command	<code>passwd -l \${Account} 2>&1</code>

8. Create a group

While defining the “Create a Group” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Group</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Group Name</i>
Mapping	<i>\${Group.Name}</i>
Description	<i><Name of the group></i>

Command Code

Field Name	Value
Shell Command	<code>groupadd \${Group} 2>&1</code>

9. Delete a group

While defining the “delete a Group” verb, certain parameters need to be defined. The following tables will help you define these parameters. Each table is dedicated to one parameter.

Command Input Parameters

Field Name	Value
Parameter Name	<i>Group</i>
Type	<i>STRING</i>
Default Value	<i>None</i>
Is the parameter required?	Yes
Is the parameter encrypted?	No
Display Name	<i>Group Name</i>
Mapping	<code>\${Group.Name}</code>
Description	<i><Name of the group></i>

Command Code

Field Name	Value
------------	-------

Shell Command	<code>groupdel \${Group} 2>&1</code>
---------------	---

COPYRIGHTS

Copyright © 2015 EMC Corporation. All Rights Reserved. Published in the USA.

TRADEMARKS

RSA, the RSA Logo, and EMC are either registered trademarks or trademarks of EMC Corporation in the United States and/or other countries. All other trademarks used herein are the property of their respective owners. For a list of EMC trademarks, go to www.rsa.com/legal/trademarks_list.pdf.